

## Federal Communications Commission

## § 27.55

(1) On all frequencies between 769–775 MHz and 799–805 MHz, by a factor not less than  $76 + 10 \log (P)$  dB in a 6.25 kHz band segment, for base and fixed stations;

(2) On all frequencies between 769–775 MHz and 799–805 MHz, by a factor not less than  $65 + 10 \log (P)$  dB in a 6.25 kHz band segment, for mobile and portable stations;

(3) On any frequency between 775–788 MHz, above 805 MHz, and below 758 MHz, by at least  $43 + 10 \log (P)$  dB;

(4) Compliance with the provisions of paragraphs (d)(1) and (d)(2) of this section is based on the use of measurement instrumentation such that the reading taken with any resolution bandwidth setting should be adjusted to indicate spectral energy in a 6.25 kHz segment;

(5) Compliance with the provisions of paragraph (d)(3) of this section is based on the use of measurement instrumentation employing a resolution bandwidth of 100 kHz or greater. However, in the 100 kHz bands immediately outside and adjacent to the frequency block, a resolution bandwidth of at least 30 kHz may be employed.

(e) For operations in the 775–776 MHz and 805–806 MHz bands, transmitters must comply with either paragraphs (e)(1) to (e)(5) of this section or the ACP emission limitations set forth in paragraphs (e)(6) to (e)(9) of this section.

(1) On all frequencies between 763–775 MHz and 793–805 MHz, the power of any emission outside the licensee's frequency bands of operation shall be attenuated below the transmitter power (P) within the licensed band(s) of operation, measured in watts, by a factor not less than  $76 + 10 \log (P)$  dB in a 6.25 kHz band segment, for base and fixed stations;

(2) On all frequencies between 763–775 MHz and 793–805 MHz, the power of any emission outside the licensee's frequency bands of operation shall be attenuated below the transmitter power (P) within the licensed band(s) of operation, measured in watts, by a factor not less than  $65 + 10 \log (P)$  dB in a 6.25 kHz band segment, for mobile and portable stations;

(3) On any frequency outside the 775–776 MHz and 805–806 MHz bands, the power of any emission shall be attenuated outside the band below the transmitter power (P) within the licensed band(s) of operation, measured in watts, by at least  $43 + 10 \log (P)$  dB;

(4) Compliance with the provisions of paragraphs (e)(1) and (e)(2) of this section is based on the use of measurement instrumentation such that the reading taken with any resolution bandwidth setting should be adjusted to indicate spectral energy in a 6.25 kHz segment;

(5) Compliance with the provisions of paragraph (e)(3) of this section is based on the use of measurement instrumentation employing a resolution bandwidth of 100 kHz or greater. However, in the 100 kHz bands im-

mediately outside and adjacent to the frequency block, a resolution bandwidth of at least 30 kHz may be employed.

\* \* \* \* \*

(f) For operations in the 746–763 MHz, 775–793 MHz, and 805–806 MHz bands, emissions in the band 1559–1610 MHz shall be limited to –70 dBW/MHz equivalent isotropically radiated power (EIRP) for wideband signals, and –80 dBW EIRP for discrete emissions of less than 700 Hz bandwidth. For the purpose of equipment authorization, a transmitter shall be tested with an antenna that is representative of the type that will be used with the equipment in normal operation.

\* \* \* \* \*

### § 27.54 Frequency stability.

The frequency stability shall be sufficient to ensure that the fundamental emissions stay within the authorized bands of operation.

### § 27.55 Signal strength limits.

(a) *Field strength limits.* For the following bands, the predicted or measured median field strength at any location on the geographical border of a licensee's service area shall not exceed the value specified unless the adjacent affected service area licensee(s) agree(s) to a different field strength. This value applies to both the initially offered service areas and to partitioned service areas.

(1) 2110–2155, 2305–2320 and 2345–2360 MHz bands: 47 dB $\mu$ V/m.

(2) 698–764 and 776–794 MHz bands: 40 dB $\mu$ V/m.

(3) The paired 1392–1395 MHz and 1432–1435 MHz bands and the unpaired 1390–1392 MHz band (1.4 GHz band): 47 dB $\mu$ V/m.

(4) BRS and EBS: The predicted or measured median field strength at any location on the geographical border of a licensee's service area shall not exceed the value specified unless the adjacent affected service area licensee(s) agree(s) to a different field strength. This value applies to both the initially offered services areas and to partitioned services areas. Licensees may exceed this signal level where there is no affected licensee that is constructed and providing service. Once the affected licensee is providing service, the original licensee will be required to